

# Rigid Conduit Bodies with Cover and Gasket

## Threaded T Type

### Features

- Threaded T type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

### Applications

- Provides access to conductors for pulling, splicing and maintenance

### Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber

### Standard Finish

- Powder coat


### Applicable Third Party Standards

- UL Standard: UL 514A - UL 514D
- Fed. Spec: W-C-586D, A-A-50563
- NEMA: FB 1-2014 - NEMA 3R



E195124

UL Standard: 514A  
Fed. Spec. W-C-586D  
NEMA FB 1



| Catalog Number | UPC   | Size          | Wire Size   |           | Unit Carton | Ship Case | Weight/Case | Inches |       |       |
|----------------|-------|---------------|-------------|-----------|-------------|-----------|-------------|--------|-------|-------|
|                |       |               | Max. Number | Max. Size |             |           |             | A      | B     | C     |
| <b>T1CG</b>    | 21731 | <b>1/2"</b>   | 1           | 6 AWG     | 10          | 100       | 38          | 4.72   | 1.37  | 1.33  |
| <b>T2CG</b>    | 21741 | <b>3/4"</b>   | 2           | 6 AWG     | 10          | 50        | 30          | 5.57   | 1.625 | 1.54  |
| <b>T3CG</b>    | 21751 | <b>1"</b>     | 3           | 6 AWG     | 5           | 25        | 20          | 6.46   | 1.90  | 1.74  |
| <b>T4CG</b>    | 21761 | <b>1-1/4"</b> | 3           | 2 AWG     | 2           | 10        | 19          | 8.528  | 2.77  | 2.49  |
| <b>T5CG</b>    | 21771 | <b>1-1/2"</b> | 3           | 2 AWG     | 2           | 10        | 21          | 8.528  | 2.77  | 2.49  |
| <b>T6CG</b>    | 21781 | <b>2"</b>     | 3           | 2/O AWG   | ---         | 5         | 10          | 10.831 | 3.335 | 3.10  |
| <b>T7CG</b>    | 21791 | <b>2-1/2"</b> | 3           | 4/O AWG   | ---         | 1         | 4           | 13.50  | 4.06  | 5.825 |
| <b>T8CG</b>    | 21801 | <b>3"</b>     | 3           | 250 MCM   | ---         | 1         | 5           | 13.50  | 4.685 | 5.825 |
| <b>T9CG</b>    | 21811 | <b>3-1/2"</b> | 3           | 350 MCM   | ---         | 1         | 12          | 15.937 | 5.45  | 7.06  |
| <b>T10CG</b>   | 21821 | <b>4"</b>     | 4           | 350 MCM   | ---         | 1         | 9           | 15.937 | 5.45  | 7.06  |