

Rigid Couplings

Compression Type - Malleable Iron

Features

- Compression type couplings
- Threadless
- Concrete tight
- Suitable for use with UL 6 Rigid Conduit

Applications

- Dry location only
- Use to join two lengths of unthreaded Rigid or IMC Conduit

Standard Material


- Malleable iron

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
251M	85528	1/2"	10	100	16	1.81	1.50
252M	85529	3/4"	10	100	24	1.87	1.62
253M	85530	1"	5	50	48	2.18	2
254M	85531	1-1/4"	5	50	86	2.62	2.37
255M	85532	1-1/2"	---	12	125	2.68	2.62
256M	85533	2"	---	5	160	3	3.31
257	12131	2-1/2"	---	5	260	5.75	3.93
258	12141	3"	---	3	300	5.72	4.66
259	12151	3-1/2"	---	2	350	6	5.20
260	12161	4"	---	2	400	6.81	5.75
260A	01495	5"	---	1	9	6.86	6.10
260B	01496	6"	---	1	12	8.14	6.81