

# Rigid Conduit Bodies

## Threaded LB Type - Malleable Iron

### Features

- NPT tapered hubs
- Suitable for use in concrete

### Applications

- Provides access to conductors for pulling, splicing and maintenance

### Standard Material


- Malleable iron

### Standard Finish

- Zinc plated, aluminum enameled



UL Standard: 514A  
Fed. Spec. W-C 586D  
NEMA FB 1



| Catalog Number | UPC   | Size          | Wire Size   |           | Ship Case | Weight/<br>Case | Inches |      |      |
|----------------|-------|---------------|-------------|-----------|-----------|-----------------|--------|------|------|
|                |       |               | Max. Number | Max. Size |           |                 | A      | B    | C    |
| <b>LB1M</b>    | 20940 | <b>1/2"</b>   | ---         | ---       | 10        | 7               | 4.56   | 2.06 | 1.31 |
| <b>LB2M</b>    | 20950 | <b>3/4"</b>   | 3           | 6 AWG     | 10        | 9               | 5.31   | 2.37 | 1.48 |
| <b>LB3M</b>    | 20960 | <b>1"</b>     | 3           | 4 AWG     | 5         | 6               | 6.25   | 2.63 | 1.75 |
| <b>LB4M</b>    | 20970 | <b>1-1/4"</b> | 3           | 2 AWG     | 5         | 23              | 8.22   | 3.50 | 2.40 |
| <b>LB5M</b>    | 20980 | <b>1-1/2"</b> | 3           | 1/0 AWG   | 10        | 26              | 8.22   | 3.75 | 2.40 |
| <b>LB6M</b>    | 20990 | <b>2"</b>     | 3           | 4/0 AWG   | 5         | 26              | 10.48  | 4.31 | 3.05 |
| <b>LB7M</b>    | 21000 | <b>2-1/2"</b> | 3           | 300 MCM   | 1         | 10              | 13.75  | 4.45 | 4.38 |
| <b>LB8M</b>    | 21010 | <b>3"</b>     | 3           | 350 MCM   | 1         | 13              | 13.75  | 4.45 | 4.38 |
| <b>LB9M</b>    | 21020 | <b>3-1/2"</b> | 3           | 500 MCM   | 1         | 22              | 16.75  | 5.80 | 5.63 |
| <b>LB10M</b>   | 21030 | <b>4"</b>     | 3           | 500 MCM   | 1         | 24              | 16.75  | 5.80 | 5.63 |