

# Rigid Raintight Couplings

## Compression Type - Malleable Iron

### Features

- Raintight and concrete tight
- Compression type couplings
- Threadless
- Suitable for use with UL 6 & UL 6A Rigid Conduit
- For use with steel or aluminum conduit
- EZ slip on labor saving design
- No disassembly required

### Applications


- Use to join two lengths of unthreaded Rigid or IMC Conduit

### Standard Material

- Malleable iron

### Standard Finish

- Zinc plated



| Catalog Number | UPC   | Size          | Unit Carton | Ship Case | Weight/ Case | Inches |      |
|----------------|-------|---------------|-------------|-----------|--------------|--------|------|
|                |       |               |             |           |              | A      | B    |
| <b>251MRT</b>  | 02127 | <b>1/2"</b>   | 10          | 100       | 32           | 2.16   | 1.45 |
| <b>252MRT</b>  | 02128 | <b>3/4"</b>   | 10          | 100       | 40           | 2.3    | 1.68 |
| <b>253MRT</b>  | 02129 | <b>1"</b>     | 5           | 50        | 29           | 2.68   | 1.93 |
| <b>254MRT</b>  | 02130 | <b>1-1/4"</b> | 5           | 50        | 42           | 3.02   | 2.34 |
| <b>255MRT</b>  | 02131 | <b>1-1/2"</b> | ---         | 12        | 13           | 3.16   | 2.56 |
| <b>256MRT</b>  | 02133 | <b>2"</b>     | ---         | 5         | 9            | 3.33   | 3.14 |
| <b>257MRT</b>  | 02134 | <b>2-1/2"</b> | ---         | 5         | 17           | 4.38   | 3.83 |
| <b>258MRT</b>  | 02135 | <b>3"</b>     | ---         | 3         | 12           | 4.74   | 4.46 |
| <b>259MRT</b>  | 02137 | <b>3-1/2"</b> | ---         | 2         | 11           | 4.86   | 5.01 |
| <b>260MRT</b>  | 02141 | <b>4"</b>     | ---         | 2         | 12           | 5.29   | 5.53 |