

Rigid Conduit Bodies

Threaded LR Type

Features

- Threaded LR type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast

Standard Finish

- Powder coat



UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
LR1	21240	1/2"	1	6 AWG	10	100	29	4.295	1.37	2.03
LR2	21250	3/4"	2	6 AWG	10	50	24	5.09	1.625	2.33
LR3	21260	1"	3	6 AWG	5	25	19	5.915	1.90	2.65
LR4	21270	1-1/4"	3	2 AWG	2	10	14	7.894	2.77	3.385
LR5	21280	1-1/2"	3	2 AWG	2	10	17	7.894	2.77	3.385
LR6	21290	2"	3	2/0 AWG	1	5	14	10.134	3.335	3.81
LR7	21300	2-1/2"	3	4/0 AWG	---	1	6	13.50	4.063	5.709
LR8	21310	3"	3	250 MCM	---	1	6	12.75	4.682	5.506
LR9	21320	3-1/2"	3	350 MCM	---	1	8	15.50	5.452	6.171
LR10	21330	4"	4	350 MCM	---	1	8	15.50	5.452	6.171