

EMT and Rigid Combination Conduit Bodies with Covers and Gaskets

TB Type

Features

- Combination TB type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- NEMA FB 1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber


Standard Finish

- Powder coat



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Max. Number	Max. Size	Unit Carton	Ship Case	Weight/Case	A	B	Inches C
TB1SSCG	17572	1/2"	1	6 AWG	10	100	38	5.35	1.31	2.02
TB2SSCG	17573	3/4"	2	6 AWG	10	50	30	6	1.62	2.22
TB3SSCG	17574	1"	3	6 AWG	5	25	18	7.06	1.88	2.56
TB4SSCG	17575	1-1/4"	3	2 AWG	2	10	17	7.25	2.50	3.50
TB5SSCG	17576	1-1/2"	3	2 AWG	2	10	19	9.25	2.67	3.50
TB6SSCG	17577	2"	3	2/O AWG	---	5	14	11.50	3.29	4.25