

Wire Connectors

Fluted Body

Features

- Easy installation
- Flame retardant; temperature rating of 105° C
- Color coded for easy size and capacity identification
- Square wire spring insert for secure connections

Applications

- Positive grip design is ideal for insulating two or more conductors
- Reusable for easy circuit changes

Standard Material

- Polypropylene



Catalog Number	UPC	Color	Unit Carton	Ship Case	Weight/ Case	Wire Range		
						Min.	Max.	Volts
Joins #22 through #14 AWG								
W81G1	30520	Gray	100/Box	5000	4	2#22	2#16	300V
W81G2	30530	Gray	500/Bag	5000	4	2#22	2#16	300V
Joins #22 through #14 AWG								
W82B1	30540	Blue	100/Box	5000	5	2#18	3#16	300V
W82B2	30550	Blue	500/Bag	5000	5	2#18	3#16	300V
Joins #22 through #14 AWG								
W8301	30560	Orange	100/Box	5000	13	2#18	2#14	600V
W8302	30570	Orange	500/Bag	5000	13	2#18	2#14	600V
Joins #18 through #10 AWG								
W84Y1	30580	Yellow	100/Box	5000	24	3#18	4#14&1#18	600V
W84Y2	30590	Yellow	500/Bag	5000	24	3#18	4#14&1#18	600V
Joins #18 through #8 AWG								
W86R1	30600	Red	100/Box	5000	52	2#14	4#12	600V
W86R2	30610	Red	500/Bag	5000	52	2#14	4#12	600V