

Rigid Conduit Bodies

Threaded LB Type

Features

- Threaded LB type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast

Standard Finish

- Powder coat



UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Max. Number	Wire Size	Unit Carton	Ship Case	Weight/Case	Inches		
				Max. Size				A	B	C
LB1	20840	1/2"	1	6 AWG	10	100	28	4.295	2.15	1.33
LB2	20850	3/4"	2	6 AWG	10	50	19	5.09	2.43	1.54
LB3	20860	1"	3	6 AWG	5	25	18	5.915	2.765	1.74
LB4	20870	1-1/4"	3	2 AWG	2	10	13	7.894	3.665	2.49
LB5	20880	1-1/2"	3	2 AWG	2	10	14	7.894	3.665	2.49
LB6	20890	2"	3	2/0 AWG	1	5	13	10.134	4.275	3.10
LB7	20900	2-1/2"	3	2/0 AWG	---	1	3	12.50	5.437	4.45
LB8	20910	3"	3	4/0 AWG	---	1	4	12.50	5.675	4.45
LB9	20920	3-1/2"	3	400 MCM	---	1	7	15.50	6.922	5.50
LB10	20930	4"	3	400 MCM	---	1	7	15.50	6.922	5.50