

Job Name/Title: _____ Catalog Number _____
Contractor: _____ Notes: _____

LED Mini-Reflectors

GU10 Series

Features

- Up to 80% Energy Savings
- No Mercury
- Last up to 10x longer than incandescent
- Dims to 10%*

Specs

- 120V
- 35° Beam Spread
- 80 CRI
- 25,000 Average Rated Life
- -20°C/-4°C Minimum Start Temperature

Applications

- Ideal for track lighting



GU10 Base



Catalog Number	Order Code	UPC	CCT	Wattage	Lumens	CBCP	MOL	Equiv. Wattage	Case Qty
LGU10/5/827/D-62	79372	751338009950	2700K	5W	350	595	2.13"	50W	1/10/100
LGU10/5/830/D-62	79374	751338009967	3000K	5W	350	595	2.13"	50W	1/10/100
LGU10/5/840/D-62	79376	751338009974	4000K	5W	350	595	2.13"	50W	1/10/100
LGU10/5/850/D-62	79378	751338009981	5000K	5W	350	595	2.13"	50W	1/10/100
LGU10/7/827/D-62	79381	751338009998	2700K	7W	500	1,231	2.25"	75W	1/10/100
LGU10/7/830/D-62	79383	751338010000	3000K	7W	500	1,231	2.25"	75W	1/10/100
LGU10/7/840/D-62	79385	751338010031	4000K	7W	500	1,231	2.25"	75W	1/10/100
LGU10/7/850/D-62	79387	751338010048	5000K	7W	500	1,231	2.25"	75W	1/10/100

Not for sale in residential new construction in California.

Specifications are subject to change without prior notice.

Not for use in enclosed fixtures

*Compatible with most leading edge or LED dimmers. Visit www.topaz-usa.com for up-to-date dimmer compatibility information.