

# STAINLESS STEEL GROUNDING HUBS


## Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Designed for use with stainless threaded conduit
- Use of neoprene O-ring assures weatherproof seal
- Includes a type 316 stainless steel locknut for a secure installation
- No package quantity required



## Applications:

To connect threaded stainless conduit to a threadless opening in a box or enclosure in an outdoor or indoor location. To positively bond conduit to a box or enclosure.



| Part Number | Trade Size (in) | A (in) | B (in) | Width (in) | Thread Length (in) | Grounding Screw (in) | Weight per each (lb) |
|-------------|-----------------|--------|--------|------------|--------------------|----------------------|----------------------|
| S60500LTV2  | ½               | 1.666  | 0.954  | 1.700      | 0.639              | 10-32 x ¾"           | 0.390                |
| S60700LTV2  | ¾               | 1.686  | 0.959  | 1.931      | 0.639              | 10-32 x ¾"           | 0.530                |
| S61000LTV2  | 1               | 2.040  | 1.120  | 2.204      | 0.795              | ¼"-20 x ½"           | 0.750                |
| S61200LTV2  | 1 ¼             | 2.084  | 1.125  | 2.564      | 0.795              | ¼"-20 x ½"           | 0.970                |
| S61500LTV2  | 1 ½             | 2.084  | 1.130  | 2.800      | 0.795              | ¼"-20 x ½"           | 1.170                |
| S62000LTV2  | 2               | 2.110  | 1.135  | 3.335      | 0.795              | ⅝"-18 x ½"           | 1.650                |
| S62500LTV2  | 2 ½             | 2.985  | 1.520  | 3.905      | 1.175              | ⅝"-18 x ½"           | 2.250                |
| S63000LTV2  | 3               | 3.045  | 1.525  | 4.600      | 1.175              | ⅝"-18 x ½"           | 3.000                |
| S64000LTV2  | 4               | 3.150  | 1.530  | 5.600      | 1.175              | ⅝"-18 x ½"           | 4.860                |

All dimensions are for informational purposes only \*Tolerances +/- 5%

