



Upside Down Marking Paints-Alert Orange, 17 Wt Oz

No. 18204 | Item# 1005224 | Case# 1005223

Product Description

Clearly and effectively marks the location of underground utilities. Colors meet the A.P.W.A. One Call International Color Standards. Safe to use on turf grass, fields, and golf courses.

Color

Alert Orange

Applications

To identify and code surfaces such as metal, concrete, asphalt, gravel, soil, trees and grass for construction, utility, recreational, municipal and landscaping sites, golf courses, nurseries and surveying.

Unit Package Description

20 Ounce Aerosol

Brand

CRC

Generic Description 1

Upside Down Marking Paints

Net Fill

17 Wt Oz

UPC Code

078254182049

Unit Dimensions

9.25H x 2.63W x 2.63D in

Units Per Case

6

Case Dimensions

10.18H x 5.6W x 11.3D in

Cases Per Pallet

136

Case Weight

8 lbs

I 2 of 5 Code

30078254182040

Appearance

Orange Liquid

Flash point (F)

-2°F

Flash point (C)

-19°C

Flammability Class - CPSC

Extremely Flammable

Spec Gravity Concentrate

0.77 to 0.85

Plastic Safe

Yes

Dry Time - Fully Dry

1 Hour

Dry Time - Tack Free

30 Minutes

Coverage

0 to 700 Linear Feet

Propellant

Hydrocarbon

Last revised: 7/23/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	51.2
VOC g/L (Consumer Product def)	529.4
VOC lbs/gal (Consumer Prod def)	4.42
VOC Category	Aerosol Coating: Ground Traffic/Marking
MIR Limit (EPA)	1.2
MIR Limit (CA)	0.85
MIR Value	0.58
Removal (How To)	Remove: WET paint with mineral spirits or turpentine, DRY paint with lacquer thinner/stripper.

