



Perma-Mend™ UV Curable Repair Patch

No. 14089 | Item# 1004826 | Case# 1004825

Product Description	Light activated fiberglass reinforced self adhesive repair patch.
Applications	Repair of tanks, pipes, roofs, steps, switch boxes, radiators, mufflers, bumpers, boat bodies. Can be used on any wood, metal, glass, ceramic, concrete and plastic surface.
Unit Package Description	3" x 6" Patch
Brand	CRC
Generic Description 1	Repair Patch
Net Fill	3" x 6"
UPC Code	078254140896
Unit Dimensions	3H x 6W
Units Per Case	12
Case Dimensions	9.75H x 2.5W x 6.5D in
Cases Per Pallet	140
Case Weight	10 lbs
I 2 of 5 Code	30078254140897
Appearance	Grey Sheet Lamination
Flash point (F)	840°F
Flash point (C)	449°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.91
Plastic Safe	Yes
Evaporation Rate	None
Curing Time	5 Minutes (Sunny), 50 Minutes (Cloudy)
Dielectric Strength	9 kV/mm
Working Temp (F)	-40 to 392°F
Working Temp (C)	-40 to 200°C
DOT Proper Shipping Name	Not Regulated

Last revised: 10/8/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



VOC % (Consumer Product def)	0.6
VOC g / L (Consumer Product def)	Not Determined
VOC lbs / gal (Consumer Prod def)	Not Determined
VOC Category	Not Regulated

