

GUJ Conduit Outlet Boxes

Explosionproof, Dust-Ignitionproof

NEC/CEC:

Class I, Division 1 and 2, Groups B♦, C, D
Class I, Zone 1 and 2, Groups IIA, IIB
Class II, Division 1 and 2, Groups E, F, G
Class III
NEMA 3, 4

Applications

- To provide access to conductors for pulling, splicing, maintenance and future changes/ upgrades.
- Allows connection of straight conduit runs, branch conduit runs and 90° bends.

Features

- Smooth hub bushings protect insulation when pulling conductors.
- Cast-in brackets on cover for use with breaker-bar tools for tightening/loosening.
- No risk of conductor insulation damage from threads on base during pulling.
- No risk of “pinching” conductors during cover installation.
- Improved wiring room
- Tapered threaded hubs (NPT)
- Dome cover available
- Internal ground screw standard
- Suitable for wet locations in upright position only.

Standard Materials

- Bodies: ductile iron

Standard Finishes

- Bodies and covers: triple-coat — (1) zinc electroplate, (2) chromate, and (3) epoxy powder coat

Options

- Hot dip or mechanical galvanized. Add suffix **-G** to standard catalog number. Contact your local representative for pricing and availability.

NEC/CEC Certifications and Compliances

- UL Standard: UL 886 (UL 1203)
- UL Listed: E-85310
- CSA Standard: CSA: C22.2 No. 30
- CSA Certified: 020945, 025875



GUJT



GUJL



GUJC



GUJLB






GUJX

♦ In Class I, Division 1, Group B atmospheres, all conduit runs must have a sealing fitting (not supplied) field-installed within 2" to the enclosure.

GUJ Conduit Outlet Boxes

Explosionproof, Dust-Ignitionproof

NEC/CEC:
 Class I, Division 1 and 2, Groups B♦, C, D
 Class I, Zone 1 and 2, Groups IIA, IIB
 Class II, Division 1 and 2, Groups E, F, G
 Class III
 NEMA 3, 4

	Trade Size (Inches)	Dimensions in Millimeter (Inches)					Cover Opening	Volume dm ³ (in ³)	Catalog Number		
		A	B	C	D	E			Malleable Iron Cover/Body ①	Malleable Iron Cover/ Body with Ground Screw/Lug ②	
Type GUJT											
	1/2	50.80 (2.00)	98.43 (3.88)	19.05 (0.75)	15.88 (0.63)	50.80 (2.00)	76.20 (3.00)	0.22 (13.50)	GUJT-50	GUJT-50 CS	
	3/4	57.15 (2.25)	98.43 (3.88)	19.05 (0.75)	19.05 (0.75)	53.98 (2.13)	76.20 (3.00)	0.25 (15.00)	GUJT-75	GUJT-75CS	
	1	63.50 (2.50)	98.43 (3.88)	22.25 (0.88)	22.35 (0.88)	60.33 (2.38)	76.20 (3.00)	0.28 (17.00)	GUJT-100	GUJT-100CS	
Type GUJL											
	1/2	50.80 (2.00)	98.43 (3.875)	19.05 (0.75)	15.88 (0.63)	50.80 (2.00)	76.20 (3.00)	0.22 (13.50)	GUJL-50	GUJL-50CS	
	3/4	57.15 (2.25)	98.43 (3.88)	19.05 (0.75)	19.05 (0.75)	53.98 (2.13)	76.20 (3.00)	0.25 (15.00)	GUJL-75	GUJL-75CS	
	1	63.50 (2.50)	98.43 (3.88)	22.25 (0.88)	22.25 (0.88)	60.33 (2.38)	76.20 (3.00)	0.28 (17.00)	GUJL-100	GUJL-100CS	
Type GUJC											
	1/2	50.80 (2.00)	98.43 (3.875)	19.05 (0.75)	15.88 (0.63)	50.80 (2.00)	76.20 (3.00)	0.22 (13.50)	GUJC-50	GUJC-50CS	
	3/4	57.15 (2.25)	98.43 (3.88)	19.05 (0.75)	19.05 (0.75)	53.98 (2.13)	76.20 (3.00)	0.25 (15.00)	GUJC-75	GUJC-75CS	
	1	63.50 (2.50)	98.43 (3.88)	22.25 (0.88)	22.35 (0.88)	60.33 (2.38)	76.20 (3.00)	0.28 (17.00)	GUJC-100	GUJC-100CS	

♦ In Class I, Division 1, Group B atmospheres, all conduit runs must have a sealing fitting (not supplied) field-installed within 2" to the enclosure.



① UL Listed outlet box with Malleable Iron Cover and Malleable Iron Body.

② UL Listed and CSA Certified outlet box with Malleable Iron Cover and Malleable Iron Body with Ground Screw/Lug.

GUJ Conduit Outlet Boxes

Explosionproof, Dust-Ignitionproof

NEC/CEC:
 Class I, Division 1 and 2, Groups B♦, C, D
 Class I, Zone 1 and 2, Groups IIA, IIB
 Class II, Division 1 and 2, Groups E, F, G
 Class III
 NEMA 3, 4

	Dimensions in Millimeters (Inches)								Catalog Number	
	Trade Size (Inches)	A	B	C	D	E	Cover Opening	Volume dm ³ (in ³)	Malleable Iron Cover/Body ①	Malleable Iron Cover/Body with Ground Screw/Lug ②
Type GUJLB										
	1/2	50.8 (2.00)	98.43 (3.88)	19.05 (0.75)	15.88 (0.63)	15.88 (0.63)	76.20 (3.00)	0.22 (13.50)	GUJLB-50	GUJLB-50CS
	3/4	57.15 (2.25)	98.43 (3.88)	19.05 (0.75)	19.05 (0.75)	19.05 (0.75)	76.20 (3.00)	0.25 (15.00)	GUJLB-75	GUJLB-75CS
	1	63.50 (2.50)	98.43 (3.88)	22.35 (0.88)	22.23 (0.88)	22.23 (0.88)	76.20 (3.00)	0.28 (17.00)	GUJLB-100	GUJLB-100CS
Type GUJX										
	1/2	50.80 (2.00)	98.43 (3.88)	19.05 (0.75)	15.88 (0.63)	50.80 (2.00)	76.20 (3.00)	0.22 (13.50)	GUJX-50	GUJX-50CS
	3/4	57.15 (2.25)	98.43 (3.88)	19.05 (0.75)	19.05 (0.75)	53.98 (2.13)	76.20 (3.00)	0.25 (15.00)	GUJX-75	GUJX-75CS
	1	63.50 (2.50)	98.43 (3.88)	22.35 (0.88)	22.35 (0.88)	60.325 (2.38)	76.20 (3.00)	0.28 (17.00)	GUJX-100	GUJX-100CS

♦ In Class I, Division 1, Group B atmospheres, all conduit runs must have a sealing fitting (not supplied) field-installed within 2" to the enclosure.

① UL Listed outlet box with Malleable Iron Cover and Malleable Iron Body.

② UL Listed and CSA Certified outlet box with Malleable Iron Cover and Malleable Iron Body with Ground Screw/Lug.