

Cable, Cord and Hose Reels



Features and Benefits

inREACH™ Industrial Weatherproof Cord Reels

- UL Type 4
- 600V AC, SOW Type Cable
- Durable, corrosion resistant cast aluminum construction design with yellow or white powder coat finish
- Multi-position guide arm
- Positive-latch mechanism automatically maintains desired cord length
- 16–10 AWG, 3 & 4 conductor cord for greater current carrying capacity



HBLW45103



HBLW45163W



HBLW35143



HBLW45103



HBLIMB



HBLI340PB



HBLI16BS

inREACH™ Industrial Weatherproof Cord Reels

Description	Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight Lbs. (kg)	Yellow Reel	White Reel
Weatherproof Industrial Reel	10	600	45 (13.7)	16/3 SOW	23.6 (10.7)	HBLW45163	HBLW45163W
				16/4 SOW	25.6 (11.6)	HBLW45164	HBLW45164W
			35 (10.7)	16/3 SOW	22.5 (10.2)	HBLW35163	HBLW35163W
				16/4 SOW	23.1 (10.5)	HBLW35164	HBLW35164W
			25 (7.6)	16/3 SOW	21.4 (9.7)	HBLW25163	HBLW25163W
				16/4 SOW	21.8 (9.9)	HBLW25164	HBLW25164W
Weatherproof Industrial Reel	15	600	45 (13.7)	14/3 SOW	28.2 (12.8)	HBLW45143	HBLW45143W
				14/4 SOW	30.0 (13.6)	HBLW45144	HBLW45144W
			35 (10.7)	14/3 SOW	25.1 (11.4)	HBLW35143	HBLW35143W
				14/4 SOW	26.5 (12.0)	HBLW35144	HBLW35144W
			25 (7.6)	14/3 SOW	22.5 (10.2)	HBLW25143	HBLW25143W
				14/4 SOW	24.3 (11.0)	HBLW25144	HBLW25144W
Weatherproof Industrial Reel	20	600	45 (13.7)	12/3 SOW	31.3 (14.2)	HBLW45123	HBLW45123W
				12/4 SOW	32.2 (14.6)	HBLW40124	HBLW40124W
			35 (10.7)	12/3 SOW	28.9 (13.1)	HBLW35123	HBLW35123W
				12/4 SOW	30.6 (13.9)	HBLW35124	HBLW35124W
			25 (7.6)	12/3 SOW	24.9 (11.3)	HBLW25123	HBLW25123W
				12/4 SOW	27.6 (12.5)	HBLW25124	HBLW25124W
Weatherproof Industrial Reel	30	600	40 (12.2)	10/3 SOW	33.3 (15.1)	HBLW40103	HBLW40103W
				10/4 SOW	34.2 (15.5)	HBLW35103	HBLW35103W
			35 (10.7)	10/3 SOW	31.7 (14.4)	HBLW35104	HBLW35104W
				10/4 SOW	34.2 (15.5)	HBLW35104	HBLW35104W
			25 (7.6)	10/3 SOW	28.4 (12.9)	HBLW25103	HBLW25103W
				10/4 SOW	30.2 (13.7)	HBLW25104	HBLW25104W

inREACH™ Accessories

Description	Weight Lbs. (kg)	Catalog Number
Mounting bracket	2.5 (1.1)	HBLIMB
340° pivot base	3.5 (1.1)	HBLI340PB
Replacement stop.	.2 (.09)	HBLI16BS HBLI14BS HBLI12BS HBLI10BS

Labor Savings are inREACH™!



Dimensions in Inches (mm)