

Hubbellok® Devices
 Switched Safety Enclosures
 Switched Enclosure
 Features

- Accommodates 30-Amp, 4 Wire Hubbellock Receptacle
- Type 3R Rainproof or 12K Dust-tight
- Molded Valox Resists Abuse, Corrosion and Enhances Safety
- Lockable Handle Meets OSHA Lockout Requirements

Ordering Information

Description	Device Color	UPC	Catalog Number
Switched enclosure for use with 3 pole 4 wire 30A Hubbellock receptacle	Gray	783585006000	SEHBL3

Listings

Listed to UL Standard
 CSA Certified Type 3R and 12K Enclosure Rating

Specifications

Base	PBT
Top	PBT
Handle	PBT
Conduit Hub	Zinc 3/4" watertight
Enclosure Gasket	Neoprene
Shaft	PBT

Performance

600V RMS	
Electrical	Operations
Electrical	
Current Interrupting	Certified for current interrupting at full rated current and voltage
Dielectric Voltage	Withstands 3,000V minimum
Environmental	Max. Working Voltage
External fully adjustable	
Mechanical	Product Identification
Identification and ratings	
Mechanical	Terminal Identification
In accordance with UL	
Mechanical	Mounting
In accordance with UL,	
Environmental	Flammability
IP54 suitability	
Environmental	Operating Temperature
Maximum continuous	
Environmental	UV Resistance
Mechanical 10,000	
Mechanical	Impact Resistance
UL94 – 5 VA and V0	
Environmental	Moisture Resistance

HUBBELL



Accessories

All materials are UV stabilized Receptacle Accommodation

Resources

eCatalog

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

