

## Straight Male Cord Connectors

**IP66\***  
SUITABILITY

Form Size 5-8



### Straight Male

NPT Hub Size	Cord Diameter Inches (mm)	Form Size	Cast Aluminum	Malleable Iron
1	.88"-1.00" (22.2-25.4)	F5	<b>SHC1046</b>	—
	1.00"-1.13" (25.4-28.6)		<b>SHC1047**</b>	—
	1.13"-1.25" (28.6-31.7)		<b>SHC1048**</b>	—
	1.25"-1.38" (31.7-34.9)		<b>SHC1049**</b>	—
1¼	.75"-.88" (19.0-22.2)	F5	<b>SHC1050</b>	—
	.88"-1.00" (22.2-25.4)		<b>SHC1051</b>	—
	1.00"-1.13" (25.4-28.6)		<b>SHC1052</b>	<b>SHC1052ZP</b>
	1.13"-1.25" (28.6-31.7)		<b>SHC1053</b>	<b>SHC1053ZP</b>
1½	1.25"-1.38" (31.7-34.9)	F5	<b>SHC1054**</b>	<b>SHC1054ZP</b>
	.75"-.88" (19.0-22.2)		<b>SHC1055</b>	—
	.88"-1.00" (22.2-25.4)		<b>SHC1056</b>	—
	1.00"-1.13" (25.4-28.6)		<b>SHC1057</b>	<b>SHC1057ZP</b>
1½	1.13"-1.25" (28.6-31.7)	F5	<b>SHC1058</b>	<b>SHC1058ZP</b>
	1.25"-1.38" (31.7-34.9)		<b>SHC1059</b>	<b>SHC1059ZP</b>
	1.38"-1.50" (34.9-38.1)		<b>SHC1061</b>	—
	1.50"-1.63" (38.1-41.3)		<b>SHC1062**</b>	—
2	1.63"-1.75" (41.3-44.4)	F6	<b>SHC1063**</b>	—
	1.75"-1.88" (44.4-47.6)		<b>SHC1064**</b>	—
	1.25"-1.38" (31.7-34.9)		<b>SHC1065</b>	—
	1.38"-1.50" (34.9-38.1)		<b>SHC1066</b>	—
2	1.50"-1.63" (38.1-41.3)	F6	<b>SHC1067</b>	—
	1.63"-1.75" (41.3-44.4)		<b>SHC1068</b>	—
	1.75"-1.88" (44.4-47.6)		<b>SHC1069</b>	—
	1.69"-1.81" (42.9-46.0)		<b>SHC1070</b>	—
2	1.81"-1.94" (46.0-49.2)	F7	<b>SHC1071</b>	—
	1.94"-2.06" (49.2-52.4)		<b>SHC1072**</b>	—
	2.06"-2.19" (52.4-55.6)		<b>SHC1073**</b>	—
	2.19"-2.31" (55.6-58.7)		<b>SHC1074**</b>	—
2½	1.69"-1.81" (42.9-46.0)	F7	<b>SHC1076</b>	—
	1.81"-1.94" (46.0-49.2)		<b>SHC1077</b>	—
	1.94"-2.06" (49.2-52.4)		<b>SHC1078</b>	—
	2.06"-2.19" (52.4-55.6)		<b>SHC1079</b>	—
3	2.19"-2.31" (55.6-58.7)	F7	<b>SHC1080</b>	—
	2.31"-2.44" (58.7-61.9)		<b>SHC1081**</b>	—
	1.69"-1.81" (42.9-46.0)		<b>SHC1086</b>	—
	1.94"-2.06" (49.2-52.4)		<b>SHC1088</b>	—
3	2.06"-2.19" (52.4-55.6)	F7	<b>SHC1089</b>	—
	2.19"-2.31" (55.6-58.7)		<b>SHC1090</b>	—
	2.31"-2.44" (58.7-61.9)		<b>SHC1091</b>	—
	2.44"-2.63" (61.9-66.7)		<b>SHC1092</b>	—
3	2.63"-2.81" (66.7-71.4)	F8	<b>SHC1093</b>	—
	2.81"-3.00" (71.4-76.2)		<b>SHC1094</b>	—
	3.00"-3.25" (76.2-82.5)		<b>SHC1095**</b>	—

Note: See pages X-78 to X-88 for technical information and dimensional drawings.

\*IP66 Suitability when used with optional metal clad O-ring, see page X-75 for additional information.

\*\*Cable jacket may have to be stripped to pass through connector body.

Locknuts sold separately. See page X-75 for additional information.