



LINKOSITY® UL Type 3R and 4X Rated Assemblies

- Available with switch, ground fault, corrosion resistant or isolated ground receptacles
- Power pass thru option
- UL Type 3R and 4X Rated
- Device identification marking
- Versatile mounting provision
- LINKOSITY® connection



LINKOSITY® Feed - UL Type 3R Rated*

3R Rated Standard Items

Description	Catalog Number
20A 125V Ground Fault	M3R002SGGF0
20A 125V Switched, Spec Grade	M3RSL1SG000
20A 125V Switched, Ground Fault	M3RSL1SGGF0
20A 125V Spec Grade	M3R002SG000
20A 125V Ground Fault, Pass-Thru	M3R002SGGFP
20A 125V Switched, Spec Grade, Pass-Thru	M3RSL1SG00P
20A 125V Switched, Ground Fault, Pass-Thru	M3RSL1SGGFP
20A 125V (2) Switches	M3R2SG000
20A 125V 1-Gang Ground Fault	M3R001SGGF0
20A 125V Corrosion Resistant	M3R002CR000
20A 125V Isolated Ground	M3R002SGIGP
20A 125V Spec Grade, Pass-Thru	M3R002SG00P

Note: *When cover closed.



Device Type	Style	Type	No. of Devices	Device Type	Device Feature	Pass-Thru
M	3R - 3R Lids 3D - 3R Deep Cover	SL - Switch Local SM - Switch Master 00 - None	1 2	SG - Spec Grade HG - Hospital Grade CR - Corrosion Resistant L1 - 15A Locking	IG - Isolated Ground GF - Ground Fault SI - Surge/IG SS - Surge 00 - Standard	P - Pass-Thru 0 - No Pass-Thru

Replacement Mounting Feet

Description	Catalog Number
For Power Distribution Assemblies.	HBLRFT1^Δ

Note: ^Δ Package of 10 mounting feet and 10 screws.

