

Kellems® Wire Management Products

Features and Benefits

PolyTuff® I and PolyTuff® II Non-Metallic Liquidtight Conduit

All non-metallic construction ends fatigue and separation problems. They can be cut cleanly with a knife or PVC cutter so there are no jagged metal edges.



PolyTuff® I Conduit, Gray

- Rigid PVC core bonded to flexible PVC jacket
- Approved for outdoor use and direct burial
- UL Listed and CSA Certified



PolyTuff® II Tubing, Black

- PVC core with corrugated walls bonded to PVC jacket
- Handles twists, turns, bends, switchbacks and straightaways with ease
- UL Recognized and CSA Certified

PolyTuff® I Conduit

IP66
SUITABILITY



| Trade Size (metric designator) | Feet (m) | Catalog Number |
|--------------------------------|--------------|-------------------|
| ¾ (12) | 100 (30.5) | G1038 |
| | 1200 (365.8) | G1038R1200 |
| ½ (16) | 100 (30.5) | G1050 |
| | 1000 (304.8) | G1050R1000 |
| ¾ (21) | 100 (30.5) | G1075 |
| | 800 (343.8) | G1075R800 |
| 1 (27) | 100 (30.5) | G1100 |
| | 500 (152.4) | G1100R500 |
| 1¼ (35) | 100 (30.5) | G1125 |
| 1½ (41) | 50 (15.2) | G1150 |
| 2 (53) | 50 (15.2) | G1200 |

Note: See pages X-58 and X-59, X-90 and X-91 for approved fittings.
See pages X-92 and X-93 for technical information and dimensional drawings.



PolyTuff® II Tubing

IP66
SUITABILITY



| Trade Size (metric designator) | Feet (m) | Catalog Number |
|--------------------------------|------------|----------------|
| ¼ (10) | 100 (30.5) | B2025 |
| ¾ (12) | 100 (30.5) | B2038 |
| ½ (16) | 100 (30.5) | B2050 |
| ¾ (21) | 100 (30.5) | B2075 |
| 1 (27) | 100 (30.5) | B2100 |
| 1¼ (35) | 100 (30.5) | B2125 |
| 1½ (41) | 50 (15.2) | B2150 |
| 2 (53) | 50 (15.2) | B2200 |

Note: See page X-90 for approved fittings.
See pages X-92 and X-93 for technical information and dimensional drawings.

