

Features and Benefits

Commercial Tamper and Weather Resistant GFCI Receptacles

- Patented shutter design for tamper-resistant protection
- Meets NEC® requirements for TR (517-18c) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® self test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired



GFTWRST83WIG



15A 125V
NEMA 5-15R
UL CSA
0.5 HP



20A 125V
NEMA 5-20R
UL CSA
1 HP



Hospital Grade • Tamper-Resistant and Weather Resistant GFCI Receptacles

Description	Rating	Color	Catalog Number			
Standard, Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Almond	GFTWRST82AL	GFTWRST83AL		
		Black	GFTWRST82BK	GFTWRST83BK		
		Brown	GFTWRST82	GFTWRST83		
		Gray	GFTWRST82GY	GFTWRST83GY		
		Ivory	GFTWRST82I	GFTWRST83I		
		Light Almond	GFTWRST82LA	GFTWRST83LA		
		Red	GFTWRST82R	GFTWRST83R		
		White	GFTWRST82W	GFTWRST83W		
		Assembled in USA, Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Almond	GFTWRST82ALU	GFTWRST83ALU
				Black	GFTWRST82BKU	GFTWRST83BKU
Brown	GFTWRST82U			GFTWRST83U		
Gray	GFTWRST82GYU			GFTWRST83GYU		
Ivory	GFTWRST82IU			GFTWRST83IU		
Light Almond	GFTWRST82LAU			GFTWRST83LAU		
Red	GFTWRST82RU			GFTWRST83RU		
White	GFTWRST82WU			GFTWRST83WU		
Isolated Ground, Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC			Almond	GFTWRST82ALIG	GFTWRST83ALIG
				Black	GFTWRST82BKIG	GFTWRST83BKIG
		Brown	GFTWRST82IG	GFTWRST83IG		
		Gray	GFTWRST82GYIG	GFTWRST83GYIG		
		Ivory	GFTWRST82IIG	GFTWRST83IIG		
		Light Almond	GFTWRST82LAIG	GFTWRST83LAIG		
		Orange	GFTWRST82ORIG	GFTWRST83ORIG		
		Red	GFTWRST82RIG	GFTWRST83RIG		
		White	GFTWRST82WIG	GFTWRST83WIG		
		SNAPConnect®, Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Almond	GFTWRST82SNAPAL	GFTWRST83SNAPAL
Black	GFTWRST82SNAPBK			GFTWRST83SNAPBK		
Brown	GFTWRST82SNAP			GFTWRST83SNAP		
Gray	GFTWRST82SNAPGY			GFTWRST83SNAPGY		
Ivory	GFTWRST82SNAPI			GFTWRST83SNAPI		
Light Almond	GFTWRST82SNAPLA			GFTWRST83SNAPLA		
Red	GFTWRST82SNAPR			GFTWRST83SNAPR		
White	GFTWRST82SNAPW			GFTWRST83SNAPW		

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color nylon wallplate, 20 amp feed-through capability. See page Tech-10 for Tamper-Resistant and Weather Resistant descriptions.

SNAPConnect® Right Angle Pigtailed Connector

Description	Wire Type	General Use	Assembled in USA
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material.	Solid	SNAP1RA	SNAP1RNA
	Stranded	SNAP2RA	SNAP2RNA
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material with WAGO terminals.	Solid	SNAP1RAM2	SNAP1RNAM2
	Stranded	SNAP2RAM2	SNAP2RNAM2

Note: For Assembled in USA products, must order connector with NA suffix. NEC® is a registered trademark of the National Fire Protection Association (NFPA).



GFTWRST82AL



GFTWRST83GYU



GFTWRST82BKIG



GFTWRST83SNAPI



SNAP1RA