



SKU: PG402-2S-Z

UPC: 0783669730302

Features & Benefits:

Description: Aluminum Parallel Groove Clamp, Dual Rated, Double Clamp, Conductor Range 4/0-2, 3/8in Steel Bolt

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	2
Number of Poles	1
Wire Orientation	Parallel

Dimensions

Drive Size Main	9/16
Drive Type Main	External Hex
Height (IN)	1.75
Height (mm)	44.45
Length (IN)	3.031
Length (mm)	76.9874
Weight (LB)	0.303789928527552
Width (IN)	1.719
Width (mm)	43.6626

Material and Finish

Clamping Hardware Material	Steel
Conductor Material	Copper
Connector Finish	Clear
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Clamping Bolt Size	3/8
Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	2

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366973030

Testing Standards

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

Color

Color

Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	4/0 Str - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA