



SKU: FX-BG24

UPC: 0783669016307

Features & Benefits:

Description: Copper Flex Braid Connector, Conductor Equivalent Size 300, 1 Braid, 24in, 2 Holes, 3/8in Bolt Size, 1in Hole Spacing, Tin Plated, UL/cUL

Specs

Additional Class Attributes

Circular Mills/Braid	336000
Mounting Hole Type	Thru
Number of Braids	1
Number of Mounting Holes	2
Shape Of Conductor	Flat

Conductor Ranges

Wire Equivalent	300 kcmil
-----------------	-----------

Dimensions

Dimension G (IN)	0.75
Dimension G (mm)	19.05
Height (IN)	0.364
Height BX (IN)	4
Length (IN)	24
Length of Ferrule (IN)	2.5
Length of Ferrule (mm)	63.5
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.41
Mounting Hole Diameter (mm)	10.414
Mounting Hole Spacing (IN)	1
Mounting Hole Spacing (mm)	25.4
Weight (LB)	3.10801610441233
Weight BX (LB)	1.632
Width (IN)	1.63
Width BX (IN)	4

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366901630

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL/cUL 467 Listed
UL File Number	E34440

Environment and Temperature

Temperature Rating	NA
--------------------	----

Additional Technical Specifications

Connector Amperage Rating AL (Derated where applicable)	NA
Connector Amperage Rating CU (Derated where applicable)	340 Amps
Conductor Type	Braid