

IMAGE
COMING
SOON

SKU: NRBRD-10-38-P25

UPC: 0783669209044

Features & Benefits:

Description:ILSCON Ring Terminal, Conductor Range 10-12, Double Crimp, 3/8in Bolt Size, Nylon Insulated, Yellow Color Code, Pack of 25

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
ILSCOs Die Index Number	B
Installation Tooling	ILST-22K
Installing Dies	Die Set B
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.252
Mounting Bolt/Stud Size (mm)	965.2
Weight (LB)	0.2292
Weight BX (LB)	13.7531
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation Material	Nylon
	Copper

General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No

NEMA Code	S-588-3
UPC Code	78366920904

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	20U0
UL / CULUS Specification	UL/cUL 486A/B Listed
UL File Number	E6207

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 12 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 12 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Halogen Free	Yes
Temperature Rating	105°C