

SKU: VBST-10-P25

UPC: 0783669213621

Features & Benefits:

Description:ILSCON Butt Splice, Conductor Range 10-12, Vinyl Insulated, Butted Barrel, Yellow Color Code, Pack of 25



Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Butted
ILSCOs Die Index Number	A
Installation Tooling	ILST-22K
Installing Dies	Die Set A
Insulation Flared End	Yes
Mounting Hole Type	NA
Number of Conductors	1

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.252
Weight (LB)	0.2103
Weight BX (LB)	12.6155
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	Yes
Insulation	Vinyl
Material	Copper

General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366921362

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	20U0
UL / CULUS Specification	UL/cUL 486A/B Listed
UL File Number	E6207

Color

Color	Yellow
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 12 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 12 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------

Environment and Temperature

Halogen Free	No
Temperature Rating	75°C