



SKU: SLUH-125

UPC: 0783669841404

Features & Benefits:

Description: Copper Mechanical Heavy Duty Lug Offset, Conductor Range 1/0-8, 1 Port, 1 Hole, 1/4in Bolt Size, UL, CSA

Specs

Additional Class Attributes

Collar Style	V-Bottom
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.438
Dimension G (mm)	11.1252
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	1.278
Height BX (IN)	2
Height (mm)	32.4612
Length (IN)	1.925
Length (mm)	48.895
Mounting Hole Diameter (IN)	0.266
Mounting Hole Diameter (mm)	6.7564
Tang Length (IN)	0.813
Tang Length (mm)	20.6502
Tang Offset (IN)	0.563
Tang Offset (mm)	14.3002
Tang Thickness (IN)	0.125
Tang Thickness (mm)	3.175
Tang Width (IN)	0.658
Tang Width (mm)	16.7132
Weight (LB)	0.115
Weight BX (LB)	5.917
Width (IN)	0.658
Width BX (IN)	6.1875
Width (mm)	16.7132

Material and Finish

Conductor Material

Copper

Connector Finish	Tin
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Brass

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/4
Wire Binding Torque	8 AWG = 40

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366984140

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA



Flex Conductor Range
Wire Combinations

1-6 G,H,I,K,M,DLO
NA

Voltage

Voltage Rating

35 kV