

SKU: T4A4-600N

UPC: 0783669912265

Features & Benefits:

Description: Aluminum Mechanical Lug, Conductor Range 600-2, 4 Ports, 10 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Tin Plated, UL, CSA



Fig. 1



Fig. 2



Fig. 3



Fig. 4

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	4
Number of Mounting Holes	10
Number of Poles	1
Number of Ports / Wireways	4

Dimensions

Dimension G (IN)	0.563
Dimension G (mm)	14.3002
Drive Size Main	1/2
Drive Type Main	Internal Hex
Height (IN)	1.5
Height BX (IN)	2
Length (IN)	5.5
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Tang Length (IN)	3.25
Tang Length (mm)	82.55
Tang Thickness (IN)	0.375
Tang Thickness (mm)	9.525
Tang Width (IN)	5
Tang Width (mm)	127
Weight (LB)	1.644
Weight BX (LB)	1.7912
Width (IN)	5
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum

Voltage

Voltage Rating

35 kV