



SKU: NFIMT-18-250-P25

UPC: 0783669207163

Features & Benefits:

Description:ILSCON Disconnect Terminal, Conductor Range 18-22, Male, Nylon Fully Insulated, Red Color Code, 0.250 x .032in Tab Size, Pack of 25

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Butted
End Connection	Male
ILSCOs Die Index Number	C
Installation Tooling	ILST-22K
Installing Dies	Die Set C
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	NA
Number of Conductors	1
Tongue Type	Disconnect

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.157
Weight (LB)	0.1326
Weight BX (LB)	7.9556
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	Yes
Insulation	Nylon
Material	Brass

General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3



UPC Code

78366920716

Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

19X5

UL / CULUS Specification

UL/cUL 310 Listed

UL File Number

E474613

Color

Color

Red

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

18 Sol - 22 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

18 Str - 22 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

300 V

Environment and Temperature

Halogen Free

Yes

Temperature Rating

105°C