



SKU: AU-1000

UPC: 0783669006995

Features & Benefits:

Description: Aluminum Mechanical Lug, Conductor Range 1000-500, 2 Ports, 1 Hole, 5/8in Bolt Size, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	2
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Dimension G (IN)	0.875
Drive Size Main	9/16
Drive Type Main	Internal Hex
Height (IN)	1.938
Height BX (IN)	2
Height (mm)	49.2252
Length (IN)	3.375
Length (mm)	85.725
Mounting Hole Diameter (IN)	0.656
Mounting Hole Diameter (mm)	16.6624
Mounting Hole Spacing (mm)	0
Tang Length (IN)	1.75
Tang Length (mm)	44.45
Tang Thickness (IN)	0.5
Tang Thickness (mm)	12.7
Tang Width (IN)	3.188
Tang Width (mm)	80.9752
Weight (LB)	1.115
Weight BX (LB)	3.4945
Width (IN)	3.188
Width BX (IN)	6.1875
Width (mm)	80.9752

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum

Voltage

Voltage Rating

35 kV