



SKU: XT-4

UPC: 0783669957556

Features & Benefits:

Description: Copper Mechanical Lug, Conductor Range 4-14, 1 Port, 1 Hole, 1/4in Bolt Size, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.25
Dimension G (mm)	6.35
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.575
Height BX (IN)	2.25
Height (mm)	14.605
Length (IN)	1.12
Mounting Hole Diameter (IN)	0.265
Mounting Hole Diameter (mm)	6.731
Tang Length (IN)	0.51
Tang Length (mm)	12.954
Tang Offset (IN)	0.072
Tang Offset (mm)	1.8288
Tang Thickness (IN)	0.082
Tang Thickness (mm)	2.0828
Tang Width (IN)	0.5
Tang Width (mm)	12.7
Weight (LB)	0.034
Weight BX (LB)	4.35
Width (IN)	0.5
Width BX (IN)	5

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

Voltage

Voltage Rating

35 kV