



SKU: ASN-400

UPC: 0783669184839

Features & Benefits:

Description: Surecrimp Aluminum Compression Sleeve, Conductor Size 400, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Index Number	472
Number of Conductors	1
Sight Window	No
Slotted	No

Dimensions

Height (IN)	1.188
Height BX (IN)	2.25
Height (mm)	30.1752
Inside Diameter (IN)	0.762
Inside Diameter (mm)	19.3548
Length (IN)	4.606
Length (mm)	116.9924
Outside Diameter (IN)	1.188
Outside Diameter (mm)	30.1752
Weight (LB)	0.288
Weight BX (LB)	0.9844
Width (IN)	1.188
Width BX (IN)	4.25
Width (mm)	30.1752

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	400 kcmil
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	400 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	400 kcmil - 4/0 Str
Flex Conductor Range	NA

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366918483

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	Green

Voltage

Voltage Rating	35 kV
----------------	-------