

IMAGE
COMING
SOON

SKU: T252/12N24

UPC: 0783669920642

Features & Benefits:

Description: Copper Flex Braid Connector, 1 Braid, 24in, 2 Holes, 1/2in Bolt Size, Tin Plated

Specs

Additional Class Attributes

Circular Mils/Braid	77184
Mounting Hole Type	Thru
Number of Braids	1
Number of Mounting Holes	2
Shape Of Conductor	Flat

Dimensions

Height (IN)	0
Height BX (IN)	2.75
Length (IN)	24
Length (mm)	609.6
Mounting Bolt/Stud Size (mm)	304.8
Thickness (IN)	0.25
Thickness (mm)	6.35
Weight (LB)	2.5063
Weight BX (LB)	2.6713
Width (IN)	1
Width BX (IN)	5
Width (mm)	25.4

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366992064

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P

Environment and Temperature

Temperature Rating	NA
--------------------	----

Additional Technical Specifications

Connector Amperage Rating AL (Derated where applicable)	NA
Connector Amperage Rating CU (Derated where applicable)	200 Amps
Conductor Type	Braid