

IMAGE
COMING
SOON

SKU: VRBR-10-14-P25

UPC: 0783669215359

Features & Benefits:

Description:ILSCON Ring Terminal, Conductor Range 10-12, 1/4in Bolt Size, Vinyl Insulated, Yellow Color Code, Pack of 25

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Brazed
ILSCOs Die Index Number	A
Installation Tooling	ILST-22K
Installing Dies	Die Set A
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.252
Weight (LB)	0.1986
Weight BX (LB)	11.9144
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	Vinyl
Material	Copper

General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3



UPC Code

78366921535

Bolt and Screw Sizes

Mounting Bolt/Stud Size

1/4

Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

20U0

UL / CULUS Specification

UL/cUL 486A/B Listed

UL File Number

E6207

Color

Color

Yellow

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

10 Sol - 12 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

10 Str - 12 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

600 V

Environment and Temperature

Halogen Free

No

Temperature Rating

105°C