



SKU: AK-350

UPC: 0783669008364

Features & Benefits:

Description: Aluminum Split Bolt, Main Range 350-1/0, Tap Range 350-4, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Poles	1

Dimensions

Drive Size Main	1-1/2
Drive Type Main	External Hex
Height (IN)	1.5
Height BX (IN)	2.25
Length (IN)	3.24
Weight (LB)	0.4562
Weight BX (LB)	0.614
Width (IN)	1.69
Width BX (IN)	4.375

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA
Wire Binding Torque	650

General

Bag Quantity	1
--------------	---

Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366900836

Testing Standards

CSA File Number	72632
CSA Standard	C22.2 No. 65
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	670B
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
---------------------------	------

Color

Color	Silver
--------------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 1/0 Str COMPACT
Conductor Range AL Stranded (Secondary, tap, load)	350 kcmil - 4 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 1/0 Str COMPACT
Conductor Range CU Stranded (Secondary, tap, load)	350 kcmil - 4 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	35 kV
-----------------------	-------