



SKU: UCS-3/0-Z

UPC: 0783669929683

Features & Benefits:

Description: Aluminum Utility Compression Sleeve, Dual Rated, Conductor Size 3/0

Specs

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Index Number	13
Installing Dies	840
Sight Window	No

Dimensions

Height (IN)	0.906
Height BX (IN)	2.75
Height (mm)	23.0124
Inside Diameter (IN)	0.49
Inside Diameter (mm)	12.446
Length (IN)	4.3
Length (mm)	109.22
Outside Diameter (IN)	0.906
Weight (LB)	0.182181964627415
Weight BX (LB)	2.243
Width (IN)	0.906
Width BX (IN)	5
Width (mm)	23.0124

Material and Finish

Conductor Material	Copper
Connector Finish	Wax
Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366992968

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	NA

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	3/0 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	3/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA