

IMAGE
COMING
SOON

SKU: NBFT-14-156-P50

UPC: 0783669203622

Features & Benefits:

Description:ILSCON Bullet Disconnect Terminal, Conductor Range 14-16, Female, Nylon Insulated, Blue Color Code, Pack of 50

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Butted
End Connection	Female
ILSCOs Die Index Number	C
Installation Tooling	ILST-22K
Installing Dies	Die Set C
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	NA
Number of Conductors	1
Tongue Type	Bullet Disconnect

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.177
Weight (LB)	0.1867
Weight BX (LB)	11.2001
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	Nylon
Material	Brass

General

Bag Quantity	50
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3



UPC Code

78366920362

Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

NA

UL / CULUS Specification

UL/cUL 1977 Recognized

UL File Number

E474615

Color

Color

Blue

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

14 Sol - 16 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

14 Str - 16 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Voltage

Voltage Rating

600 V

Environment and Temperature

Halogen Free

Yes

Temperature Rating

85°C