



SKU: HT-8

UPC: 0783669461220

Features & Benefits:

Description:Aluminum Compression Tap Connector, Dual Rated, Main Conductor Range 2/0 Str - 2 Str and 3/0 Sol - 1 Sol, Tap Range 1/0 Sol - 6

Sol and 1 Str - 6 Str, CSA

Specs

| Additional Class Attributes | |
|-----------------------------|------|
| Barrel Marking | Hard |
| Fixing Type | NA |
| ILSCOs Die Index Number | 0 |
| Replacement Part(s) | NA |

| Dimensions | |
|----------------|---------|
| Height (IN) | 1.786 |
| Height BX (IN) | 8.25 |
| Height (mm) | 45.3644 |
| Length (IN) | 1.5 |
| Length (mm) | 38.1 |
| Weight (LB) | 0.084 |
| Width (IN) | 0.717 |
| Width BX (IN) | 4.6875 |
| Width (mm) | 18.2118 |

| Material and Finish | |
|---------------------|----------|
| Conductor Material | Copper |
| Connector Finish | NA |
| Insulation | NA |
| Material | Aluminum |

| Additional Technical Specifications | | |
|-------------------------------------|----------|--|
| Conductor Type | Stranded | |

| General | |
|-----------------------------|-----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 25 |
| Direct Burial | No |
| Dual Rated | Yes |
| NEMA Code | S-588-1 |
| UPC Code | 78366946122 |



Bolt and Screw Sizes

Mounting Bolt/Stud Size

Testing Standards

CSA File Number AP-5465

This product is in compliance with Prop65. It is not known to **Prop65 Compliance** contain any chemicals associated with this regulation

NA

UL Control Number UL File Number NA

Environment and Temperature

Temperature Rating 90°C

Color

Color Silver **Color Code** NA

Voltage

Voltage Rating 35 kV Voltage Rating with cover NA

Conductor Ranges

Conductor Range ACSR (Secondary, tap, load) 1/0 ACSR - 3 ACSR Conductor Range ACSR (primary, run, main, line) 2 ACSR - 6 ACSR Conductor Range AL Solid (Secondary, tap, load) 1/0 Sol - 6 Sol Conductor Range AL Stranded (Primary, run, main, line) 2/0 Str - 2 Str Conductor Range AL Stranded (Secondary, tap, load) 1 Str - 6 Str 3/0 Sol - 1 Sol Conductor Range CU Solid (Primary, run, main, line) 1/0 Sol - 6 Sol Conductor Range CU Solid (Secondary, tap, load) Conductor Range CU Stranded (Primary, run, main, line) 2/0 Str - 2 Str Conductor Range CU Stranded (Secondary, tap, load) 1 Str - 6 Str 3/0 Sol - 1 Sol Conductor Range AL Solid (Primary, run, main, line)