



SKU: SPA-1000

UPC: 0783669857122

Features & Benefits:

Description: Aluminum Splicer/Reducer, Dual Rated, Conductor Range 1000-500, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	2
Number of Poles	1
Number of Ports Tap	1
Number of Ports / Wireways	2
Wire Orientation	Parallel

Dimensions

Drive Size Main	9/16
Drive Type Main	Internal Hex
Height (IN)	1.75
Height BX (IN)	2.75
Height (mm)	44.45
Length (IN)	8.688
Length (mm)	220.6752
Tang Width (mm)	0.254
Weight (LB)	2.184
Weight BX (LB)	2.4318
Width (IN)	1.75
Width BX (IN)	6
Width (mm)	44.45

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
Number of Wire Binding Screws per Port	3
Wire Binding Screw Size	1-1/8
Wire Binding Torque	600

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366985712

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1000 kcmil - 500 kcmil
Conductor Range AL Stranded (Secondary, tap, load)	1000 kcmil - 500 kcmil
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil - 500 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	1000 kcmil - 500 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	35 kV
----------------	-------