

**SKU:** UCS-1000-Z

**UPC:** 0783669929867

**Features & Benefits:**

**Description:** Aluminum Utility Compression Sleeve, Dual Rated, Conductor Size 1000



## Specs

### Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Long
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Index Number	18
Installing Dies	72H
Sight Window	No

### Dimensions

Height (IN)	1.6
Height BX (IN)	2.25
Height (mm)	40.64
Inside Diameter (IN)	1.188
Inside Diameter (mm)	30.1752
Length (IN)	7.3
Length (mm)	185.42
Outside Diameter (IN)	1.6
Weight (LB)	0.650568687851654
Weight BX (LB)	1.489
Width (IN)	1.6
Width BX (IN)	4.25
Width (mm)	40.64

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Wax
Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366992986

### ***Bolt and Screw Sizes***

Mounting Bolt/Stud Size	NA
-------------------------	----

### ***Testing Standards***

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

### ***Environment and Temperature***

Temperature Rating	90°C
--------------------	------

### ***Color***

Color	Silver
Color Code	NA

### ***Conductor Ranges***

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1000 kcmil
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA