



SKU: VDMT-10-250-P25

UPC: 0783669214345

Features & Benefits:

Description:ILSCON Disconnect Terminal, Conductor Range 10-12, Male, Vinyl Insulated, Yellow Color Code, 0.250 x .032in Tab Size, Pack of 25

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Construction Type	Butted
End Connection	Male
ILSCOs Die Index Number	C
Installation Tooling	ILST-22K
Installing Dies	Die Set C
Insulation Flared End	Yes
Insulation Grip	Yes
Mounting Hole Type	NA
Number of Conductors	1
Tongue Type	Disconnect

Dimensions

Height (IN)	2.88
Height BX (IN)	7.75
Length (IN)	3.5
Maximum Wire Insulation Diameter (IN)	0.252
Weight (LB)	0.136
Weight BX (LB)	8.4
Width (IN)	1.21
Width BX (IN)	9.5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation Material	Vinyl
	Brass

General

Bag Quantity	25
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366921434

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	19X5
UL / CULUS Specification	UL/cUL 310 Listed
UL File Number	E474613

Color

Color	Yellow
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 12 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	10 Str - 12 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	300 V
----------------	-------

Environment and Temperature

Halogen Free	No
Temperature Rating	75°C