



SKU: CP-4-B2

UPC:

Features & Benefits:

Description: Copper Post Connector, Conductor Range 4-14, 1/4in Bolt Size, UL, CSA, Bag of 2

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.54
Height BX (IN)	2.75
Height (mm)	13.716
Length (IN)	8.4
Length (mm)	213.36
Weight (LB)	0.0711315617393328
Weight BX (LB)	4.152
Width (IN)	3
Width BX (IN)	6
Width (mm)	76.2

Material and Finish

Connector Finish	NA
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/4
Number of Wire Binding Screws per Port	1

Wire Binding Screw Size	NA
Wire Binding Torque	10 - 14 AWG = 35

General

Bag Quantity	2
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366903007

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	6 Sol - 18 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 18 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Voltage

Voltage Rating	35 kV
----------------	-------