



SKU: RLT-3

UPC: 0783669715668

Features & Benefits:

Description: Permaground Copper Grounding Connector, Main Conductor Range 2/0-2, Tap Range 2/0-2, Ground Rod Size 5/8in, Rebar Sizes #3-#4, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Catalog Number	ILD-998
ILSCOs Die Index Number	998

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	2/0 Str - 2 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	5/8
Rebar Size(s) Main	#4 (1/2)

Dimensions

Height (IN)	1.972
Height BX (IN)	4.75
Height (mm)	50.0888
Length (IN)	0.875
Length (mm)	22.225
Weight (LB)	0.4
Weight BX (LB)	8.262
Width (IN)	1.234
Width BX (IN)	7
Width (mm)	31.3436

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 20
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366971566

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-5465
CSA Standard	C22.2 No. 41
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Environment and Temperature

Temperature Rating	NA
--------------------	----

Color

Color	Copper
-------	--------