



SKU: SLS-300

UPC: 0783669824520

Features & Benefits:

Description: Copper Mechanical Lug Straight, Conductor Range 350-1/0, 1 Port, 1 Hole, 3/8in Bolt Size, UL, CSA

Specs

Additional Class Attributes

Collar Style	V-Bottom
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.5
Dimension G (mm)	12.7
Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.6
Height BX (IN)	2
Height (mm)	40.64
Length (IN)	3.188
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Tang Length (IN)	1.782
Tang Length (mm)	45.2628
Tang Thickness (IN)	0.187
Tang Thickness (mm)	4.7498
Tang Width (IN)	1
Tang Width (mm)	25.4
Weight (LB)	0.367
Weight BX (LB)	7.8943
Width (IN)	1
Width BX (IN)	6.1875

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

Voltage

Voltage Rating

35 kV