



SKU: SLUH-35

UPC: 0783669839739

Features & Benefits:

Description: Copper Mechanical Heavy Duty Lug Offset, Conductor Range 6-14, 1 Port, 1 Hole, #10in Bolt Size, UL, CSA

Specs

Additional Class Attributes

Collar Style	V-Bottom
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.227
Dimension G (mm)	5.7658
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.731
Height BX (IN)	2.25
Height (mm)	18.5674
Length (IN)	1.125
Length (mm)	28.575
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.203
Mounting Hole Diameter (mm)	5.1562
Tang Length (IN)	0.5
Tang Length (mm)	12.7
Tang Offset (IN)	0.328
Tang Offset (mm)	8.3312
Tang Thickness (IN)	0.09
Tang Thickness (mm)	2.286
Tang Width (IN)	0.375
Tang Width (mm)	9.525
Weight (LB)	1.603
Weight BX (LB)	160.32
Width (IN)	0.435
Width BX (IN)	5
Width (mm)	11.049

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Brass

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/8
Wire Binding Torque	8 - 14 AWG = 20

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366983973

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	6 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA

Conductor Range AL Solid (Primary, run, main, line)	NA
Flex Conductor Range	8 H, 8-10 I, 8-14 G,K,M,DLO
Wire Combinations	NA

Voltage

Voltage Rating	35 kV
----------------	-------