



SKU: CSWD-1000-58-112

UPC: 0783669651171

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 1000, 2 Holes, 5/8in Bolt Size, 1-1/2in Hole Spacing, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-125
ILSCOs Die Index Number	I-125
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	2
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.625
Barrel Length (mm)	41.275
Dimension G (IN)	0.671
Dimension G (mm)	17.0434
Height (IN)	1.552
Height BX (IN)	2
Height (mm)	39.4208
Inside Diameter (IN)	1.172
Inside Diameter (mm)	29.7688
Length (IN)	5.65
Length (mm)	143.51
Mounting Hole Diameter (IN)	0.656
Mounting Hole Diameter (mm)	16.6624
Mounting Hole Spacing (IN)	1.5
Mounting Hole Spacing (mm)	38.1
Outside Diameter (IN)	1.502
Outside Diameter (mm)	38.1508
Strip Length (mm)	42.8498
Tang Length (IN)	3
Tang Length (mm)	76.2
Tang Thickness (IN)	0.328
Tang Thickness (mm)	8.3312

Tang Width (IN)	2.169
Tang Width (mm)	55.0926
Weight (LB)	1.1616188505708
Weight BX (LB)	3.8257
Width (IN)	2.169
Width BX (IN)	6.1875
Width (mm)	55.0926

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	1000 kcmil - 750 kcmil
Flex Conductor Range	750 G,H,I 777.7 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366965117

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature



Temperature Rating

90°C

Color

Color

Silver

Color Code

White

Voltage

Voltage Rating

35 kV