



SKU: FX-BE24T58

UPC: 0783669017366

Features & Benefits:

Description: Copper Flex Braid Connector, Conductor Equivalent Size 3/0, 1 Braid, 24in, 1 Hole, 5/8in Bolt Size, Tin Plated, UL/cUL

Specs

Additional Class Attributes

Circular Mils/Braid	168000
Mounting Hole Type	Thru
Number of Braids	1
Number of Mounting Holes	1
Shape Of Conductor	Flat

Conductor Ranges

Wire Equivalent	3/0 AWG
-----------------	---------

Dimensions

Dimension G (IN)	0.625
Dimension G (mm)	15.875
Height (IN)	0.21
Height BX (IN)	4
Length (IN)	24
Length of Ferrule (IN)	1.25
Length of Ferrule (mm)	31.75
Mounting Hole Diameter (IN)	0.66
Mounting Hole Diameter (mm)	16.764
Weight (LB)	1.38686001518571
Weight BX (LB)	1.5
Width (IN)	1.25
Width BX (IN)	4

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1



Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366901736

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/8
-------------------------	-----

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL/cUL 467 Listed
UL File Number	E34440

Environment and Temperature

Temperature Rating	NA
--------------------	----

Additional Technical Specifications

Connector Amperage Rating AL (Derated where applicable)	NA
Connector Amperage Rating CU (Derated where applicable)	340 Amps
Conductor Type	Braid