

**MOTOR FINISH****BLADE FINISHES**

Auburn Stained



Dimmable

AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	RPM Revolutions Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
5205	183	70	75

SPECIFICATIONS

Performance			
CFM (High)	5205	RPM (High)	183
Watts (High)	70	Airflow Efficiency CFM/W (High)	75
Motor Specifications			
Amps (High)	0.59	Motor Size	172MM X 15MM
Motor Type	AC Induction	Primary Material	Steel
Mounting/Installation			
Minimum Distance from Fan to Floor	7 feet	Interior/Exterior	Interior
Lead Wire Length	78"	Location Rating	Dry
Low Ceiling Adaptable	No	Max Stem Tilt	30.00
Dimensions			
Downrod 1	1.00 OD X 6.00"	Downrod 1 - Measurement A	17.00"
Downrod 1 - Measurement B	12.50"	Downrod 1 - Measurement C	9.50"
Base Backplate	7.25 DIA	Weight	24.70 LBS
Blade Sweep	52	Height	17.00"
Width	52.00"		
Light Source			
Downlight Included	Yes	Downlight Option	Integrated
Dimmable	Yes	Color Rendering Index	80
Kelvin Temperature	3000K	Initial Lumens	1600
Lumens/watt (efficacy)	94.00	Diffuser Description	Etched Cased Opal
Downward-facing Bulbs	1 X 17W	Lamp Included	Integrated
# of Bulbs/LED Modules	1		

FIXTURE ATTRIBUTES

Blade Finish & Specs

Blade Finish 1	Auburn Stained	Blade Material	Wood
Blade Pitch	12	Blades Included	Yes
Number of Blades	5		

Included Control

Wall Control Included	Yes	Remote Included	No
Control Type	371045.00	Limited/Full Function	Full Function

Product/Ordering Information

SKU	300052DBK	Finish	Distressed Black
UPC	783927554305	Style	Transitional

Housing

Fan Primary Control System	65K Wall Control - Full Function
----------------------------	----------------------------------

Warranty

www.kichler.com/warranty

Compatible Accessories

65K CoolTouch™ Transmitter Full Function White, Wall Control System Full Function Multiple Finishes

ALSO IN THIS FAMILY



300052NI



43433AUB



43435CLP



43436CLP



43435AUB

You can see all products in this family by searching **Kichler.com**