


**MOTOR FINISH****BLADE FINISHES**

Walnut



Dimmable

**AIR PERFORMANCE**

| AIRFLOW<br>Cubic Ft. Per Minute on High | RPM<br>Revolutions Per Minute on High | POWER USAGE<br>Watts on High<br>(Excludes Lights) | AIRFLOW EFFICIENCY<br>Cubic Ft. Per Minute Per Watt |
|-----------------------------------------|---------------------------------------|---------------------------------------------------|-----------------------------------------------------|
| 4388                                    | 143                                   | 50                                                | 87                                                  |

**SPECIFICATIONS**

| Performance                        |                   |                                 |                                               |
|------------------------------------|-------------------|---------------------------------|-----------------------------------------------|
| CFM (High)                         | 4388              | RPM (High)                      | 143                                           |
| Watts (High)                       | 50                | Airflow Efficiency CFM/W (High) | 87                                            |
| Motor Specifications               |                   |                                 |                                               |
| Amps (High)                        | 0.44              | Motor Size                      | 153MM X 18MM                                  |
| Motor Type                         | AC Induction      | Primary Material                | Steel                                         |
| Mounting/Installation              |                   |                                 |                                               |
| Minimum Distance from Fan to Floor | 7 feet            | Interior/Exterior               | Interior                                      |
| Lead Wire Length                   | 78"               | Location Rating                 | CSA UL Listed Dry                             |
| Low Ceiling Adaptable              | No                | Max Stem Tilt                   | 30.00                                         |
| Dimensions                         |                   |                                 |                                               |
| Downrod 1                          | 1.00 OD X 4.50"   | Downrod 1 - Measurement A       | 14.50"                                        |
| Downrod 1 - Measurement B          | 13.25"            | Downrod 1 - Measurement C       | 6.75"                                         |
| Base Backplate                     | 5.75 DIA          | Weight                          | 17.20 LBS                                     |
| Blade Sweep                        | 52                | Height                          | 14.50"                                        |
| Width                              | 52.00"            |                                 |                                               |
| Light Source                       |                   |                                 |                                               |
| Downlight Included                 | Yes               | Downlight Option                | Removable                                     |
| Dimmable                           | Yes               | Dimmable Notes                  | Recommended for use with Kichler Fan Controls |
| Color Rendering Index              | 80                | Kelvin Temperature              | 3000K                                         |
| Initial Lumens                     | 1600              | Lumens/watt (efficacy)          | 94.00                                         |
| Diffuser Description               | Etched Cased Opal | Downward-facing Bulbs           | 1 X 17W                                       |
| Lamp Included                      | Integrated        | # of Bulbs/LED Modules          | 1                                             |
| Photometrics                       |                   |                                 |                                               |
| Color Temperature Range            | 3000              |                                 |                                               |

**FIXTURE ATTRIBUTES**

### Blade Finish & Specs

|                  |        |                 |      |
|------------------|--------|-----------------|------|
| Blade Finish 1   | Walnut | Blade Material  | SOLW |
| Blade Pitch      | 14     | Blades Included | Yes  |
| Number of Blades | 3      |                 |      |

### Included Control

|                       |           |                       |                  |
|-----------------------|-----------|-----------------------|------------------|
| Wall Control Included | Yes       | Remote Included       | No               |
| Control Type          | 370039.00 | Limited/Full Function | Limited Function |

### Product/Ordering Information

|     |              |        |                    |
|-----|--------------|--------|--------------------|
| SKU | 300027OBB    | Finish | Oil Brushed Bronze |
| UPC | 783927521390 | Style  | Transitional       |

### Housing

|                            |                               |  |
|----------------------------|-------------------------------|--|
| Fan Primary Control System | 3 Spd Wall Control Ltd Functn |  |
|----------------------------|-------------------------------|--|

### Warranty

[www.kichler.com/warranty](http://www.kichler.com/warranty)

### Compatible Accessories

CoolTouch™ Handheld Control System Limited Function White, Wall Transmitter Limited Function Multiple Finishes, Wall Control System Limited Function Multiple Finishes, CoolTouch™ Transmitter Limited Function White

### ALSO IN THIS FAMILY



300027AP



300027BSS



300027NBR

You can see all products in this family by searching **Kichler.com**