© 2022 Kichler Lighting LLC. All Rights Reserved.



MOTOR FINISH



BLADE FINISHES

Distressed Antique Gray



AR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High

5056

RPM Revolutions Per Minute on High

162

POWER USAGE Watts on High (Excludes Lights)

63

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

80

SPECIFICATIONS

Performance			
CFM (High) Watts (High)	5056 63	RPM (High) Airflow Efficiency CFM/W (High)	162 80
Motor Specifications			
Amps (High) Motor Type	0.53 AC Induction	Motor Size Primary Material	153MM X 17MM Steel
Mounting/Installation			
Minimum Distance from Fan to Floor Lead Wire Length Low Ceiling Adaptable	7 feet 78" No	Interior/Exterior Location Rating Max Stem Tilt	Interior Dry 22.00
Dimensions			
Downrod 1 Downrod 1 - Measurement B Base Backplate Blade Sweep Width	1.00 OD X 6.00" 9.00" 6.00 DIA 52 52.00"	Downrod 1 - Measurement A Downrod 1 - Measurement C Weight Height	14.50" 7.00" 13.54 LBS 14.50"
Light Source			
Downlight Included Dimmable Kelvin Temperature Lumens/watt (efficacy) Downward-facing Bulbs	Yes Yes 3000K 94.00 1 X 17W	Downlight Option Color Rendering Index Initial Lumens Diffuser Description Lamp Included	Integrated 80 1600 Etched Cased Opal Integrated

of Bulbs/LED Modules **FIXTURE ATTRIBUTES**

Blade Finish & Specs			
Blade Finish 1 Blade Pitch Number of Blades	Distressed Antique Gray 13 3	Blade Material Blades Included	ABS Yes
Included Control			
Wall Control Included Control Type	Yes 337010.00	Remote Included	No
Product/Ordering Information			
SKU UPC	300275AVI 783927559911	Finish Style	Anvil Iron Transitional
Housing			
Fan Primary Control System	Dual Slide Control		
107			

Warranty

www.kichler.com/warranty

Compatible Accessories

CoolTouch™ Handheld Control System Limited Function White, Dual Slide Control Fan and Light White, Wall Control System Limited Function Multiple Finishes

ALSO IN THIS FAMILY



You can see all products in this family by searching **Kichler.com**