


**MOTOR FINISH**

Satin Black

BLADE FINISHES


Natural Brass



Dimmable



LED Light Kit

HANGING MEASUREMENTS**AIR PERFORMANCE****AIRFLOW**

Cubic Ft. Per Minute on High

5400

RPM

Revolutions Per Minute on High

106

POWER USAGEWatts on High
(Excludes Lights)

75

AIRFLOW EFFICIENCY

Cubic Ft. Per Minute Per Watt

72

SPECIFICATIONS**Performance**

| | | | |
|--------------|------|---------------------------------|-----|
| CFM (High) | 5400 | RPM (High) | 106 |
| Watts (High) | 75 | Airflow Efficiency CFM/W (High) | 72 |

Motor Specifications

| | | | |
|-------------|--------------|------------------|--------------|
| Amps (High) | 0.63 | Motor Size | 188MM X 25MM |
| Motor Type | AC Induction | Primary Material | Steel |

Mounting/Installation

| | | | |
|------------------------------------|----------|-------------------|--------------|
| Minimum Distance from Fan to Floor | 7.0 feet | Interior/Exterior | INTERIOR |
| Lead Wire Length | 78" | Location Rating | Dry |
| Low Ceiling Adaptable | No | Max Stem Tilt | 22.0 Degrees |
| Connector | Yes | Direct Wire | Yes |
| Mounting Style | Downrod | Wire Connectors | Wire Nuts |

Dimensions

| | | | |
|---------------------------|-----------------|---------------------------|-----------|
| Downrod 1 | 1.00 OD X 4.50" | Downrod 1 - Measurement A | 14.60" |
| Downrod 1 - Measurement B | 10.00" | Downrod 1 - Measurement C | 9.50" |
| Base Backplate | 6 | Weight | 28.67 LBS |
| Blade Sweep | 54 | Height | 14.60" |
| Length | 56.00" | Width | 56.00" |

Light Source

| | | | |
|------------------------|------------|-----------------------|------------|
| Downlight Included | Yes | Downlight Option | Integrated |
| Dimmable | Yes | Color Rendering Index | 90 |
| Kelvin Temperature | 3000K | Initial Lumens | 2200 |
| Diffuser Description | Frosted | Downward-facing Bulbs | 1 X 23 |
| Lamp Included | Integrated | Light Source | LED |
| # of Bulbs/LED Modules | 1 | | |

Photometrics

| | |
|----------------------------------|----|
| Delivered Efficacy (Lumens/Watt) | 75 |
|----------------------------------|----|

| Electrical | | | |
|------------------------------------------------------------------------|-------------------------------|-----------------------|---------------|
| Input Voltage | 120.00V | Supply Wire (Degrees) | 90 |
| FIXTURE ATTRIBUTES | | | |
| Blade Finish & Specs | | | |
| Blade Finish 1 | Natural Brass | Blade Material | ABS |
| Blade Pitch | 13 | Blades Included | Yes |
| Number of Blades | 5 | | |
| Included Control | | | |
| Wall Control Included | No | Remote Included | Yes |
| Remote Type | 371085.00 | Limited/Full Function | Full Function |
| Product/Ordering Information | | | |
| SKU | 330057SBK | Finish | Satin Black |
| UPC | 783927012768.0 | Style | Industrial |
| Housing | | | |
| Fan Primary Control System | 65K Cooltouch - Full Function | Shade Description | Glass |
| Shade Dimensions | 9.50 | | |
| Warranty | | | |
| www.kichler.com/warranty | | | |
| Compatible Accessories | | | |
| CoolTouch™ Handheld Control System Full Function White | | | |

ALSO IN THIS FAMILY



330057BSS



330057WH

You can see all products in this family by searching **Kichler.com**