© 2022 Kichler Lighting LLC. All Rights Reserved.

MOTOR FINISH



Brushed Nickel

BLADE FINISHES

Weathered White Walnut



Dimmable



AR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High

5205

RPM Revolutions Per Minute on High

183

POWER USAGE Watts on High (Excludes Lights)

70

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

75

SPECIFICATIONS

Performance			
CFM (High) Watts (High)	5205 70	RPM (High) Airflow Efficiency CFM/W (High)	183 75
Motor Specifications			
Amps (High) Motor Type	0.59 AC Induction	Motor Size Primary Material	172MM X 15MM Steel
Mounting/Installation			
Minimum Distance from Fan to Floor Lead Wire Length Low Ceiling Adaptable	7 feet 78" No	Interior/Exterior Location Rating Max Stem Tilt	Interior Dry 30.00
Dimensions			
Downrod 1 Downrod 1 - Measurement B Base Backplate Blade Sweep Width	1.00 OD X 6.00" 12.50" 7.25 DIA 52 52.00"	Downrod 1 - Measurement A Downrod 1 - Measurement C Weight Height	17.00" 9.50" 24.70 LBS 17.00"
Light Source			
Downlight Included Dimmable Kelvin Temperature Lumens/watt (efficacy) Downward-facing Bulbs	Yes Yes 3000K 94.00 1 X 17W	Downlight Option Color Rendering Index Initial Lumens Diffuser Description Lamp Included	Integrated 80 1600 Etched Cased Opal Integrated

of Bulbs/LED Modules FIXTURE ATTRIBUTES

Blade Finish & Specs					
Blade Finish 1 Blade Pitch Number of Blades	Weathered White Walnut 12 5	Blade Material Blades Included	Wood Yes		
Included Control					
Wall Control Included Control Type	Yes 371045.00	Remote Included Limited/Full Function	No Full Function		
Product/Ordering Information					
SKU UPC	300052NI 783927555005	Finish Style	Brushed Nickel Transitional		
Housing					
Fan Primary Control System	65K Wall Control - Full Function				
Warranty					
www.kichler.com/warranty					
Compatible Accessories					
65K CoolTouch™ Transmitter Full Function White, Wall Control System Full Function Multiple Finishes					
ALSO IN THIS FAMILY					
300052DBK	43433	BAUB	43435CLP		
		•			

You can see all products in this family by searching **Kichler.com**

43435AUB

43436CLP