



Reflector Infrared BR40,PAR38

125BR40 IR/1/TG 120V 4/1

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. Philips Infrared lamps are suited for heating and drying in industrial and commercial aplications. These incandescent, gas-filled infrared heat lamps come up to full temperature almost immediately, eliminating costly warm-up time. Highly efficient heat generators that produce a minimum of light rays and a high amount of infrared radiation. The BR40 lamp provides a built-in reflector for radiant energy control.

Product data

General Information	
Base	E26 [Single Contact Medium Screw]
Operating Position	Universal [Universal]
Main Application	Infrared
Gas Filling	GAS
Footnote Incandescent 1	Average laboratory life in excess of 5000 hours. In-service
	life depends upon service conditions. (27)
Footnote Incandescent 2	Do not allow hot bulb to come in contact with liquid or
	metal parts of the fixture, as glass may shatter. Do not use
	outdoors. Do not operate in close proximity to flammable
	materials or those adversely affected by heat or drying.
	Operate only in heat resistant sockets. (87)
Footnote Incandescent 3	CAUTION: Do not operate in close proximity to flammable
	materials or those adversely affected by heat or drying.
	Operate only in heat resistant sockets. WARNING: Use
	carefully. May cause serious burns. Do not use over
	insensitive skin areas or in the presence of poor circulation. $ \\$
	The unattended use of infrared heat by children or

	incapacitated persons may be dangerous.—Lamp should
	not be placed closer that 18" to the surgace being irritated.
	$-\mbox{Do}$ not use dor the rapeutic or topical applications unless
	recommended by a physician.—For food warming, use only
	lamps with heat resisting glass. (89)
Footnote Incandescent 4	Circle E-The encircled E means this bulb meets Federal
	minimum efficiency standards.
Light Technical	
Beam Description	Spot
Operating and Electrical	
Power (Rated) (Nom)	125 W
Voltage (Nom)	120 V
Mechanical and Housing	
Bulb Finish	Clear
Cap-Base Information	Aluminium [Aluminium Cap]


Datasheet, 2020, October 29 data subject to change

Reflector Infrared BR40, PAR38

Filament Shape	C-9 [Pendant]
Product Data	
Order product name	125BR40 IR/1/TG 120V 4/1
EAN/UPC - Product	046677159306
Order code	159301
Numerator - Quantity Per	1
Pack	

Numerator - Packs per	4
outer box	
Material Nr. (12NC)	925254936309
Net Weight (Piece)	0.001 kg

Dimensional drawing



125W E26 120V BR40 SP CL

Product

125BR40/1/TG 120V 4/1



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.